

IN THE CLAIMS:

Claim 1 (cancelled).

Claim 2 (currently amended): ~~[[The]]~~ A vehicular headlamp according to claim 1,  
wherein comprising a lamp body, a beam radiation unit that includes a discharge bulb as a light  
source and said beam radiation unit is laterally rotatably supported in said lamp body, an  
illumination circuit unit that illuminates said discharge bulb provided in said lamp body, and a  
cord that connects said illumination circuit unit and said discharge bulb, wherein:

said cord is held at a middle portion thereof so as to be prevented from being  
moved with respect to said lamp body.

said beam radiation unit is laterally rotatable in a bracket that is inclinably  
supported in said lamp body,

said illumination circuit unit is provided below said radiation unit, and

said cord is held on an upper surface of said illumination circuit unit and in the  
vicinity of said beam radiation unit.

Claim 3 (original). The vehicular headlamp according to claim 2, wherein said cord is  
held by a clamp member that is provided on said upper surface of said illumination circuit unit.

Claim 4 (cancelled).

Claim 5 (cancelled).

Claim 6 (currently amended): ~~[[The]]~~ A vehicular headlamp according to claim 4,  
wherein comprising a lamp body, a beam radiation unit that includes a discharge bulb as a light  
source and said beam radiation unit is laterally rotatably supported in said lamp body, an  
illumination circuit unit that illuminates said discharge bulb provided in said lamp body, and a  
cord that connects said illumination circuit unit and said discharge bulb, wherein said vehicular  
headlamp is provided with a cord holding means that holds said cord between said illumination  
circuit unit and said discharge bulb to prevent said cord from moving with respect to said lamp  
body and said cord holding means comprises a clamp formed in a bracket that supports said  
beam radiation unit in said lamp body.

Claim 7 (cancelled).